

CLAIMS

1 1. A pattern matching engine for use in searching network messages for pre-
2 defined regular expressions and for determining matches thereto, the pattern matching
3 engine comprising:
4 a regular expression storage device for storing the pre-defined regular expressions
5 and one or more corresponding actions that are to be applied to network messages
6 matching the respective regular expressions, the storage device including a content-
7 addressable memory (CAM) having a plurality of entries containing at least the pre-
8 defined regular expressions; and
9 a decoder circuit coupled to the regular expression storage device, the decoder
10 circuit configured to control an input to the CAM that includes a given network message
11 or selected portion thereof for comparison with the regular expressions contained within
12 the CAM, and to receive and decode an output returned from the regular expression
13 storage device, the output identifying the action to be applied to the given network
14 message or portion thereof,
15 whereby the CAM is configured such that each network message or portion
16 thereof input to the CAM is compared against all CAM entries at the same time, allowing
17 high-speed pattern matching of network messages.

1 2. The pattern matching engine of claim 1 wherein each CAM entry further
2 contains a tag such that all CAM entries having the same tag define a single logical CAM
3 within the CAM, and further wherein the decoder circuit is configured to constrain the

4 matching of a given CAM input to the CAM entries corresponding to a selected logical
5 CAM.

1 3. The pattern matching engine of claim 2 further comprising a barrel shifter
2 operatively coupled to the decoder circuit, the barrel shifter configured to provide a
3 selected portion of a network message to the CAM input as directed by the decoder
4 circuit.

1 4. The pattern matching engine of claim 3 further comprising a second decoder
2 circuit coupled to the regular expression storage device, and a second barrel shifter
3 operatively coupled to the second decoder circuit, wherein the second decoder circuit and
4 second barrel shifter apply a selected portion of a second network message to the regular
5 expression storage device in parallel fashion with the decoder circuit and barrel shifter.

1 5. The pattern matching engine of claim 3 wherein the CAM input comprises a
2 message data space for storing the network message or portion thereof provided by the
3 barrel shifter, a tag space for storing the selected tag, and an end flag indicating whether
4 the message data space contains a last segment of the respective network message.

1 6. The pattern matching engine of claim 5 wherein the output returned by the
2 regular expression storage device comprises an operation code for identifying the action
3 to be applied to the respective network message and, to the extent further searching is to
4 be performed on the respective network message, an offset for use in directing the barrel

1 10. The pattern matching engine of claim 8 wherein a second action output by the
2 regular expression storage device is a counter action, and the pattern matching engine
3 further comprises a counter memory coupled to the decoder circuit, the counter memory
4 having one or more counters that may be selectively actuated by the decoder circuit in
5 response to the counter action.

1 15. A method for searching network messages for pre-defined regular expressions
2 in order to apply a selected action to network messages matching a given regular
3 expression, the method comprising the steps of:

4 storing the pre-defined regular expressions in a content-addressable memory
5 (CAM) having a plurality of entries;
6 associating each CAM entry with the action that corresponds to the regular
7 expression stored at the respective CAM entry;
8 inputting a given network message or selected portion thereof to the CAM for
9 comparison with all of the regular expressions stored therein; and
10 identifying the action that corresponds to a first CAM entry matching the inputted
11 network message or selected portion thereof.

1 16. The method of claim 15 wherein the step of associating comprises the step of
2 providing a second memory structure having a plurality of entries for storing the actions
3 to be applied to the network messages, wherein each entry of the second memory
4 structure is associated with a corresponding entry of the CAM and stores the action to be
5 applied to network messages matching the regular expression of its corresponding CAM
6 entry.

1 17. The method of claim 16 further comprising the step of appending a tag to the
2 given network message or selected portion thereof that is input to the CAM, and further
3 wherein each CAM entry contains a tag value such that all CAM entries having the same
4 tag value define a single logical CAM within the CAM.

1 18. The method of claim 17 wherein the CAM is a ternary content addressable
2 memory (TCAM) and the second memory structure is a random access memory (RAM).

1 19. An intermediate network device for use in processing and forwarding network
2 messages in a computer network, the intermediate network device comprising:

3 a plurality of line cards, one or more of the line cards capable of being connected
4 to portions of the computer network by respective communications media, each line card
5 configured to receive and forward network messages;

6 a message processing card; and

7 a common bus that provides inter-communication between the plurality of line
8 cards and the message processing card, wherein the message processing card comprises:

9 pattern matching engine for use in searching network messages for pre-
10 defined regular expressions and for determining matches thereto, the pattern
11 matching engine comprising:

12 a regular expression storage device for storing the pre-defined
13 regular expressions and one or more corresponding actions that are to be
14 applied to network messages matching the respective regular expressions,
15 the storage device including a content-addressable memory (CAM) having
16 a plurality of entries containing at least the pre-defined regular
17 expressions; and

18 a decoder circuit coupled to the regular expression storage device,
19 the decoder circuit configured to control an input to the CAM that includes
20 a given network message or selected portion thereof for comparison with
21 the regular expressions contained within the CAM, and to receive and
22 decode an output returned from the regular expression storage device, the

23 output identifying the action to be applied to the given network message or
24 portion thereof,

25 whereby the CAM is configured such that each network message
26 or portion thereof input to the CAM is compared against all CAM entries
27 at the same time, allowing high-speed pattern matching of network
28 messages.

1 20. The intermediate network device of claim 19 wherein each CAM entry of the
2 CAM further contains a tag such that all CAM entries having the same tag define a single
3 logical CAM within the CAM, and further wherein the decoder circuit is configured to
4 constrain the matching of a given CAM input to the CAM entries corresponding to a
5 selected logical CAM.

1 21. The intermediate network device of claim 20 wherein the pattern matching
2 engine further comprises a barrel shifter operatively coupled to the decoder circuit, the
3 barrel shifter configured to provide a selected portion of a network message to the CAM
4 input as directed by the decoder circuit.

1 22. The intermediate network device of claim 21 wherein the pattern matching
2 engine further comprises a second decoder circuit coupled to the regular expression
3 storage device, and a second barrel shifter operatively coupled to the second decoder
4 circuit, wherein the second decoder circuit and second barrel shifter apply a selected

5 portion of a second network message to the regular expression storage device in parallel
6 fashion with the decoder circuit and barrel shifter.

1 23. The intermediate network device of claim 22 wherein the CAM input
2 comprises a message data space for storing the network message or portion thereof
3 provided by the barrel shifter, a tag space for storing the selected tag, and an end flag
4 indicating whether the message data space contains a last segment of the respective
5 network message.

1 24. The intermediate network device of claim 23 wherein the output returned by
2 the regular expression storage device comprises an operation code for identifying the
3 action to be applied to the respective network message and, to the extent further
4 searching is to be performed on the respective network message, an offset for use in
5 directing the barrel shifter to select a new message portion for a subsequent CAM input
6 and a tag to be appended to the subsequent CAM input.

1 25. A pattern matching engine for use in searching network messages for pre-
2 defined regular expressions and for determining matches thereto, the pattern matching
3 engine comprising:
4 means for storing the pre-defined regular expressions and one or more
5 corresponding actions that are to be applied to network messages matching the respective
6 regular expressions, the storage means including a content-addressable memory (CAM)
7 having a plurality of entries containing at least the pre-defined regular expressions; and

48